

SANDUSKY SPEEDWAY 2017 HOBBY STOCK RULES

THE RULES AND/OR SPECIFICATIONS SET FORTH HEREIN ARE DESIGNED TO PROVIDE FOR THE ORDERLY CONDUCT OF RACING EVENTS AND TO ESTABLISH MINIMUM ACCEPTABLE REQUIREMENTS FOR SUCH EVENTS. THESE RULES SHALL GOVERN THE CONDITION OF ALL SPEEDWAY EVENTS, AND BY PARTICIPATING IN THESE EVENTS, ALL SPEEDWAY ENTRANTS ARE DEEMED TO HAVE COMPLIED WITH THESE RULES. NO EXPRESS OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF, OR COMPLIANCE WITH THESE RULES AND/OR SPECIFICATIONS. THEY ARE INTENDED AS A GUIDE FOR THE SPORT AND ARE IN NO WAY A GUARANTEE AGAINST INJURY OR DEATH TO PARTICIPANTS, SPECTATORS, OR OTHERS.

NOTICE: Creative interpretation and/or anything that may not be covered by the following rules or racing procedures are the sole responsibility of the Driver. If a question should arise a Driver should inquire with the Competition Inspector and/or Race Director before proceeding. Any decision on questionable items about rules and racing procedures is up to the Competition Inspector and/or Race Director and their decision is FINAL! Remember: It is the responsibility of the Driver to keep his/her car legal and follow all rules and racing procedures at all times. Infractions of the technical rules of any kind may result in an additional weight penalty, fine, forfeit qualifying, or not being able to compete until infraction is corrected. Penalty will be determined by the Competition Inspector and/or Race Director.

1.0 ELIGIBILITY:

- 1.1** This division is limited to 1980 to present American and Foreign passenger front wheel drive two (2) or four (4) door cars.
- 1.2** NO MITSUBISHI 3000 GTS OR STEALTHS ALLOWED. CHRYSLER PRODUCTS PERMITTED. No convertibles or two seat coupes.

2.0 BODIES/FRAMES:

- 2.1** The body and frame must be of the same make/model of vehicle being used, and must remain factory stock, including wheel wells.
- 2.2** Cars must have a grill in reasonable condition at all times.
- 2.3** Hood and Deck lid must be attached to factory hinges. Must remove hood and trunk locks and be replaced with hood pins or seat belt latches that can secure hood and deck lid.
- 2.4** All exterior chrome trim, with the exception of window moldings, must be removed.
- 2.5** Headlights, taillights and parking lights must be removed and holes filled with sheet metal.
- 2.6** Doors can be gutted out to add roll cage door bars.
- 2.7** Cars must have full front and rear firewalls, floor pan, trunk and rear packing shelf firewall. Must be original and in factory stock location. Front and rear firewalls and floor pan must have all openings and holes covered with metal. NO MODIFICATIONS.

- 2.8 Body must be presentable at all times.
- 2.9 Frame and any part of the car cannot be lower than (6") minimum ride height measured with driver in the car.

3.0 INTERIOR:

- 3.1 All flammable upholstery fabric must be removed, including back seat, carpet, head liner, door panels etc...
- 3.2 The front/rear firewall and floor pan must be original and in factory stock location. All openings must be covered with metal.
- 3.3 All interior supports must remain in factory stock location.

4.0 BUMPERS:

- 4.1 Front and rear bumpers must be stock for the car they're on. No aftermarket bumper covers allowed.
- 4.2 An external tow hook mounted in the center of the bumper, both on front and rear, capable to support the weight of the car is mandatory.
- 4.3 Radiator protection bar allowed. It must only be one (1) bar between the front bumper shocks and it must stay behind the bumper and not be exposed outside of the grill or higher than the hood when closed.

5.0 RUB RAILS:

- 5.1 Must be center line of the car between front and rear tires only. Must be secured to roll cage and be up against body and may not be larger than (2") wide and (1") thick. No sharp edges. No other bars outside of car allowed.

6.0 WINDSHIELD/MIRRORS/RADIOS/SCANNERS:

- 6.1 Must have factory stock windshield, made of **Clear** glass or (1) piece Lexan in good condition at all times.
- 6.2 Back seat left and right side windows and rear window made of **Clear** Lexan only will be permitted.
- 6.3 No rear or side view mirrors allowed. No two way radios.
- 6.4 The use of two-way radio communication is prohibited at all time.
- 6.5 A one-way receiving radio scanner locked to frequency (463.7625) is **MANDATORY** and must be operational at all times.

7.0 SEAT/SEAT BELTS:

- 7.1 Original factory front seat or a racing high back seat is allowed. If factory front seat remains, original tilt mechanism must be welded to prevent movement of the seat.
- 7.2 Original factory seat belts or approved racing belts allowed.
- 7.3 Racing seat belts must be a minimum (3) point harness and mounted securely per manufacturer's instructions.

8.0 ROLL BARS:

- 8.1 Roll bars are mandatory. roll cage must be a minimum of a four (4) point roll cage.
- 8.2 Driver's door protection is mandatory with four (4) minimum driver's door bars.
- 8.3 Material use to make the roll cage must be a minimum of (.095) material thickness by (1 ½") tubing in diameter.
- 8.4 Must have a bar going across the dash between the front bars. Must be welded to a steel plate that is welded and /or bolted to floor using the minimum of four (4) (9/16th) harden bolts on each corner of the plates with harden washers and locking nuts. Plates under floor pad should be used and bolted to roll cage mounted plates.
- 8.5 All bars around the driver must be padded.
- 8.6 No galvanized tubing permitted.

- 8.7 Absolutely no bars outside front or rear firewall.
- 8.8 No bars to rear shock towers or to the rear bumper.
- 8.9 Inner door panels can be removed for door bars of the roll cage . No other panels can be cut out.

9.0 SPOILERS/GROUND EFFECTS:

- 9.1 Spoiler and ground effects can be used ONLY if it is stock factory made for that car. No homemade/aftermarket spoilers or ground effects allowed.
- 9.2 Rocker panels must look factory stock, (NO straight down look). No fairing out of rocker panel or body panels. Must meet (6") ground clearance.

10.0 ENGINES:

- 10.1 Must be completely factory stock for make/model of car.
- 10.2 Four or six cylinder transverse mounted engines only.
- 10.3 Motors can be changed but must stay with the same type motor in the car. (GM in GM, Ford in Ford etc.)
- 10.4 Motor must bolt right in without any modifications done to car and be in factory stock location with original engine mounts.
- 10.5 Must have working alternator.
- 10.6 All non-used accessories can be removed from motor, (AC, air pump, etc.).
- 10.7 All belts must be on engine.
- 10.8 NO MODIFICATIONS OR RACING COMPONENTS! No porting or polishing on cylinder heads, intakes, or exhaust manifolds.
- 10.9 Factory computer system only! Computers may be exchanged by officials at any time. No performance enhancing chips can be used. Factory Assembly Line Diagnostic Link (ALDL) must be left in the car and in working order.
- 10.10 No turbo or superchargers will be permitted.
- 10.11 Maximum engine displacement size (3400) V6 motors with only (1) camshaft and can only be used if it came from the respective manufacture.
- 10.12 No aftermarket parts whatsoever can be used on any part of the car. If a discrepancy is found, you may be suspended and/or fined and loss of any points for that event.

11.0 EXHAUST:

- 11.1 Must be factory stock unmodified and unaltered manifold for make/model of car being used with a (2") maximum outside diameter.
- 11.2 Tailpipes must be under the car and exit out back or either side of car, but must pass behind the driver.
- 11.3 Catalytic converter and muffler may be removed. No other modifications, **no headers**.

12.0 CARBURETOR/FUEL INJECTION:

- 12.1 Must remain factory stock for make/model car being used. NO MODIFICATIONS whatsoever.
- 12.2 No larger throttle body or aftermarket injectors can be used.

13.0 AIR CLEANER/AIR INTAKE:

- 13.1 Only factory air box can be used. No cool air intake or aftermarket air boxes permitted.

14.0 RADIATOR:

- 14.1 Must be in good condition and have stock drip bottle attached to radiator in motor compartment at all times for overflow protection.
- 14.2 NO ANTIFREEZE! The use of antifreeze is prohibited and can result in a (\$100) fine.

15.0 BATTERY/IGNITION:

- 15.1 Battery may remain under the hood, or may be moved into driver's compartment. Battery that remains under the hood must have a minimum of (1") wide metal strap to hold it down.
- 15.2 Battery that's moved to the inside of driver's compartment must be mounted in a PLASTIC MARINE TYPE BOX. Battery must be securely mounted down. **NO RUBBER OR WIRE TIE DOWNS!**
- 15.3 Must be stock ignition for make and model to the car. Stock factory coils only. No aftermarket coils whatsoever.

16.0 TRANSMISSION:

- 16.1 Factory equipped automatic or manual transmission for make/model of car being used is permitted.
- 16.2 Must use a stock flywheel and clutch. No aluminum clutches or flywheels. No high performance clutches or flywheels.
- 16.3 Transmission coolers ok, must mount to radiator and be doubled clamped at each end.
- 16.4 Must have at least (3) working forward gears and (1) reverse and use factory stock gear shifter for manual transmissions and gear selector for automatic transmission.
- 16.5 NO SHIFTER RODS of any kind allowed.

17.0 SUSPENSION:

- 17.1 Must remain stock in stock location.
- 17.2 Shocks and struts must be stock. No racing springs, shocks, struts, or aftermarket parts permitted.
- 17.3 No lengthening, lower control arms or CV shafts.
- 17.4 No bending of strut tower.
- 17.5 Cambering of the right front wheel allowed, but only using existing parts . NO CAMBERING OF ANY OTHER WHEELS AT ALL OR REAR STEER.
- 17.6 No modifications can be made to the frame or body.
- 17.7 Wheelbase must be a minimum of (92") to max (105"). Wheelbase must be the same on both sides.
- 17.8 Rear springs must be stock, but must have the same height, size, and number of coils on each side. No racing, coil-over, aftermarket springs or air shocks allowed.

18.0 STEERING:

- 18.1 Must use stock components and match make and model of car being used.
- 18.2 Factory steering wheel or an aftermarket steering wheel with a quick release hub can be used and must be welded to the factory stock steering column. No other modifications to steering column is permitted.

19.0 BRAKES:

- 19.1 Must be factory stock operated hydraulic type, operating all four (4) wheels at all times.
- 19.2 Absolutely NO racing brakes of any kind. No racing or aftermarket type proportioning valves allowed.
- 19.3 No cross drilling or slotted rotors allowed.
- 19.4 Brake inspection or test can be performed at any time. If a brake test is done after the feature all brakes must be working properly or you will be disqualified.

20.0 TIRES/WHEELS:

Steel racing rims allowed, 8" max. up to 2" offset max allowed
American Racer tire only. Sizes 23/7-14"sh, 23/7-14"
24/7-15"sh, 24/7-15"

21.0 GAS TANK/FUEL:

- 21.1 Gas tank and fuel pump must remain stock and in stock location under car.
- 21.2 All gas tanks must add two (2) extra metal straps with a minimum width of (1") and running opposite stock straps (left side to right side of car).
- 21.3 Pump fuel only. No racing fuel, alcohol, nitrous, or additives allowed.

22.0 WEIGHT:

- 22.1 ADDITIONAL WEIGHT OF ANY KIND WILL NOT BE PERMITTED ON THE CAR.

23.0 PAINTING/NUMBERS:

- 23.1 All cars must be professionally painted, neat in appearance and professionally lettered at all times.
- 23.2 Numbers must be approved by the Speedway office and must be professionally painted on both sides and on the roof of car. Must be readable from the right side, in minimum twenty-four (24") heights, with a four (4") stripe width in a color offering contrast to the color of car.
- 23.3 A four (4") number with the letter (C) lettered in white or yellow located on the upper right side (Passenger Side) of the windshield.
- 23.4 All car numbers must be registered with Lorain County Speedway office regardless if number competed in previous years.

24.0 TRANSPONDER:

- 24.1 Transponder is to be mounted behind the left rear tire.

25.0 SAFETY EQUIPMENT:

- 25.1 All drivers must be protected at all times with a clean SFI or equivalent full fire driving suit, fire retardant gloves, shoes, quick-release lap belt, shoulder harness and headrest.
- 25.2 Hans, Hutchens or equivalent head and neck restraint is highly recommended.
- 25.3 A Snell-Rated helmet SA2005 or newer is required. Sticker must be visible and verifiable.
- 25.4 Harness and seat belts and are required to be five point system with lower crotch belt (six point systems are recommended). Mounting attachment bar for shoulder harness must be at shoulder height of the driver and harness should not bend or change direction. Belt systems must be minimum of (3") SFI approved units, dated within three years to date.
- 25.5 All cars must have a driver's side web style window net with a latch mechanism on the top front corner, and must fall down alongside driver's door when released.
- 25.6 All cars must have a (2 ½) pound minimum B and C dry chemical fire extinguisher with gauge mounted within easy reach of driver and in working order at all times.
- 25.7 An engine ignition kill switch must be mounted within the driver's reach and must be marked 'OFF' / 'ON'.

NOTICE/WARNING: All part numbers must be visible and unaltered. If part number is not legible or has been altered in any way it will be determined to be illegal and not permitted for use. If any items are found to be illegal, Sandusky speedway and/or its Track Officials reserve the right to confiscate any illegal parts.

Please read the above rules very carefully. If your car is built accordingly, you should have no trouble. Always ask a Competition Inspector before you proceed.

REMEMBER: Sandusky Speedway and its officials reserve the right to change specifications/procedures/competition rules, and add/or subtract cars to the field at any time. Those who sign-in and/or start in an event agree to be governed by these rules and by all decisions of the Speedway and its officials.

Any technical questions contact the Tech. Inspector **TBA**

Any procedural questions contact the Event Director **Chris** Mize 330-280-1936

